

HVAC

Product Catalog

- Condensate Removal
- Ice Machine Replacement
- Evaporative Cooler
- Accessories



Wastewater

Water Systems

HVAC

Industrial

Engineered
Products

LittleGIANT®

What's Hot!

Condensate Removal Pump: Medium Tank

1/2 gallon capacity; safety switch;
and 20' shut off.

See page 4 for more information.



VCMA-20ULS

Condensate Removal Pump: Shallow-Pan Tank

Durable thermoplastic float;
advanced mechanical switch;
and fully submersible.

See page 7 for more information.



1-ABS

Condensate Removal Pump: Recommended for air conditioners and refrigeration equipment

The Little Giant TP series of peristaltic pumps have been designed to run quieter and more efficiently than other condensate pumps. These self priming pumps automatically remove condensate water from air conditioners and refrigeration equipment.

See page 9 for more information.



TP Series

Accessories: Auxiliary Condensate Overflow Safety Switch

Low-voltage; 18" or 72" lead wire;
and can install switch to activate
audible and/or visual alarm.

See page 13 for more information.



ACS-3

See your distributor for more information,
or call Franklin Electric directly at 1-800-701-7894.

- Condensate Removal
- Ice Machine Replacement
- Evaporative Cooler
- Accessories



Table of Contents

Condensate Removal Pumps

VCMX Series	2-3
VCMA Series	4
VCC Series	5
VCL Series	5-6
ABS Series	7-8
EC Series	8
TP Series	9
EC-OP-K Series	10

Ice Machine Replacement Pumps

RIM-U Series	11
--------------------	----

Evaporative Cooler Pumps

CP Series	12
-----------------	----

Accessories

Coil Cleaning Kit	13
Safety Switches	13-14
Tubing	14
Check Valves	15

Specification Charts

Specification Charts	16
----------------------------	----

Condensate Removal Pumps

VCMX SERIES

High Capacity Model



VCMX- 20ULS

Applications

- For removal of condensate from air conditioners, suitable for high efficiency gas furnace condensation and condensing boilers

Features

- Fully automatic: start, stop, safety switch
- Check valve outlet: 3/8" (9.5 mm), for 3/8" (9.5 mm) ID
- cCSAus listed
- Options: safety switch, 20' (6 m) of 3/8" (9.5 mm) tubing and anti-sweat sleeve
- 1/30 hp high performance motor

Series Specifications


Shut Off: 21" (4.8 mm)

Maximum Liquid Temperature:
140 °F (60 °C)

Electrical: 115 V, 60 Hz, 1.5A, 93 W
230 V, 50/60 Hz, 0.60A,
75 W

Operation: Automatic

Performance Curve



Model Characteristics

NXTGen

Item #	Model	Performance (GPH @ Height in Feet)					Shut Off (ft.)	Volts	Hertz	Amps	Watts	Cord (ft.)	Check Valve	Safety Switch	Dimensions (inches)			List/Cert.
		1	5	10	15	20									Height	Length	Width	
554520	VCMX-20UL	84	75	60	42	10	21	115	60	1.5	93	6	3/8"	No	6.5	10.2	4.8	cCSAus
554521	VCMX-20UL	80	69	54	36	0	20	230	50/60	0.6/0.5	75	6	3/8"	No	6.5	10.2	4.8	cCSAus
554530	VCMX-20ULS	84	75	60	42	10	21	115	60	1.5	93	6	3/8"	Yes	6.5	10.2	4.8	cCSAus
554531	VCMX-20ULS	80	69	54	36	0	20	230	50/60	0.6/0.5	75	6	3/8"	Yes	6.5	10.2	4.8	cCSAus

NXTGen With Tubing

Item #	Model	Performance (GPH @ Height in Feet)					Shut Off (ft.)	Volts	Hertz	Amps	Watts	Cord (ft.)	Check Valve	Safety Switch	Dimensions (inches)			List/Cert.
		1	5	10	15	20									Height	Length	Width	
554550	VCMX-20ULST	84	75	60	42	10	21	115	60	1.5	93	6	3/8"	Yes	6.5	10.2	4.8	cCSAus
554551	VCMX-20ULST	80	69	54	36	0	20	230	50/60	0.6/0.5	75	6	3/8"	Yes	6.5	10.2	4.8	cCSAus

NXTGen With Anti-Sweat Sleeve

Item #	Model	Performance (GPH @ Height in Feet)					Shut Off (ft.)	Volts	Hertz	Amps	Watts	Cord (ft.)	Check Valve	Safety Switch	Dimensions (inches)			List/Cert.
		1	5	10	15	20									Height	Length	Width	
554542	VCMX-20ULS-C	84	75	60	42	10	21	115	60	1.5	93	6	3/8"	Yes	6.8	10.3	5.1	cCSAus

VCMX SERIES

High Capacity Model continued

External Overflow Safety Switch

Item #	Model	Description
599136	ACS-X10	Safety Switch with 10" Leads
599137	ACS-X72	Safety Switch with 72" Cable

Anti-Sweat Sleeve

Item #	Model	Description
599138	VCMX-CK	Tank Sleeve with Mounting Bracket

VCMX
External Safety
Switch (optional)



**Fast & easy
wall mounting**



VCMX-20ULS



VCMX-20ULST
with Tubing



VCMX-20ULS-C
with Anti-Sweat
Sleeve

**1/4-Turn
Check Valve:**
Allows servicing
without removal of
tubing, eliminating
water spills

Cooling Design:
Improved cooling
increases pump life

**Sleek and Stylish
Appearance:**
Performs as good
as it looks

**Optional External
Overflow
Safety Switch:**
Gives you the option
to connect air-handler
shutdown, or activate
an alarm or building
automation system

Slimmer Footprint:
6.5" x 10.2" x 4.8"
size offers flexibility
in tight spaces

Rubber Feet:
Absorb vibration
on hard surface
installations

**Oil-Resistant Tank
and Check Valve:**
Eliminate the problem
of cracked tanks with
exposure to oil

**External Test/
Run Lever:**
Quick test/run and
easy drainage of the
tank for servicing



Condensate Removal Pumps

VCMA SERIES Medium Tank



VCMA-15ULS

Applications

- For removal of condensate from an air conditioner, suitable for high efficiency, gas furnace condensation and condensing boilers

Features

- 1/50 hp high performance motor
- ABS tank, motor cover, and volute
- 1/2 gallon tank capacity
- Stainless steel shaft
- Snap-action switch
- Removable 3/8" (9.5 mm) barbed check valve
- 3 inlet drain holes
- Thermal overload protection
- Includes 20' (6.1 m) of 3/8" ID (9.5 mm) tubing (554411 and 554415 only)
- Safety switch (554405 and 554415 only)
- cCSAul

Series Specifications

Capacity: 65 gph @ 1'
(246 lph @ 0.31 m)

Shut Off: 15' (4.6 m)

Maximum Liquid Temperature:
140 °F (60 °C)

Discharge: 3/8" barbed (9.5 mm)


Impeller: Glass-filled polypropylene

Electrical: 115 V, 60 Hz, 1A

Operation: Automatic

Model Characteristics

Item #	Model	Volts	Cord	Capacity
554401	VCMA-15UL	115	6'	65 GPH @ 1'
			1.8 m	246 LPH @ 0.31 m
554405	VCMA-15ULS	115	6'	65 GPH @ 1'
			1.8 m	246 LPH @ 0.31 m
554411	VCMA-15ULT	115	6'	65 GPH @ 1'
			1.8 m	246 LPH @ 0.31 m
554415	VCMA-15ULST	115	6'	65 GPH @ 1'
			1.8 m	246 LPH @ 0.31 m



VCMA-20ULS

Applications

- For removal of condensate from an air conditioner, suitable for high efficiency, gas furnace condensation and condensing boilers

Features

- 1/30 hp high performance motor
- ABS tank, motor cover and volute
- 1/2 gallon tank capacity
- Stainless steel shaft
- Removable 3/8" (9.5 mm) barbed check valve
- 3 inlet drain holes
- Thermal overload protection
- Includes 20' (6.1 m) of 3/8" ID (9.5 mm) tubing (554431, 554435 and 554461 only)
- Safety switch (554435, 554425, 554455 and 554461 only)
- cCSAul

Series Specifications

Capacity: 80 gph @ 1'
(303 lph @ 0.31 m)

Shut Off: 20' (6.1 m) 115 V models
17' (5.2 m) 230 V models

Maximum Liquid Temperature:
140 °F (60 °C)

Discharge: 3/8" barbed (9.5 mm)

Impeller: Glass-filled polypropylene


Electrical: 115 V, 60 Hz, 1A

230 V, 50/60 Hz,
0.6/0.5A

Operation: Automatic

Model Characteristics

Item #	Model	Volts	Cord	Capacity
554421	VCMA-20UL	115	6'	80 GPH @ 1'
			1.8 m	303 LPH @ 0.31 m
554451	VCMA-20UL	230	6'	80 GPH @ 1'
			1.8 m	303 LPH @ 0.31 m
554425	VCMA-20ULS	115	6'	80 GPH @ 1'
			1.8 m	303 LPH @ 0.31 m
554455	VCMA-20ULS	230	6'	80 GPH @ 1'
			1.8 m	303 LPH @ 0.31 m
554431	VCMA-20ULT	115	6'	80 GPH @ 1'
			1.8 m	303 LPH @ 0.31 m
554435	VCMA-20ULST	115	6'	80 GPH @ 1'
			1.8 m	303 LPH @ 0.31 m
554461	VCMA-20ULST	230	6'	80 GPH @ 1'
			1.8 m	303 LPH @ 0.31 m



Condensate Removal Pumps

VCC SERIES Low Profile Tank

VCC-20ULS



Applications

- For removal of condensate from an air conditioner, suitable for high efficiency, gas furnace condensation

Features


- Low profile for limited space applications
- 1/30 hp motor
- ABS tank, motor cover, and volute
- 3/10 gallon tank capacity
- Stainless steel shaft
- Removable 3/8" (9.5 mm) barbed check valve
- Thermal overload protection
- Safety switch
- cCSAul

Series Specifications

Capacity: 200 gph @ 1' (757 lph @ 0.31 m)
Shut Off: 14' (4.3 m)
Liquid Temperature: 120 °F (49 °C)
Discharge: 3/8" barbed (9.5 mm)
Impeller: Polypropylene
Electrical: 115 V, 60 Hz, 1A
Operation: Automatic

Model Characteristics

Item #	Model	Volts	Cord	Capacity
554200	VCC-20ULS	115	6'	80 GPH @ 1'
			1.8 m	303 LPH @ 0.31 m
554210	VCC-20ULS	230	6'	80 GPH @ 1'
			1.8 m	303 LPH @ 0.31 m



VCL SERIES Large Tank

VCL-14ULS



Applications

- For removal of condensate from an air conditioner, suitable for high efficiency, gas furnace condensation and condensing boilers

Features


- 1/50 hp motor
- Galvanized steel tank cover
- ABS tank, volute and switch cover
- 1 gallon tank capacity
- Stainless steel shaft
- Thermal overload protection
- Safety switch
- cCSAul

Series Specifications

Capacity: 200 gph @ 1' (757 lph @ 0.31 m)
Shut Off: 14' (4.3 m)
Liquid Temperature: 120 °F (49 °C)
Discharge: 3/8" barbed (9.5 mm)
Impeller: Polypropylene
Electrical: 115 V, 60 Hz, 1A
Operation: Automatic

Model Characteristics

Item #	Model	Volts	Cord	Capacity
553101	VCL-14ULS	115	6'	200 GPH @ 1'
			1.8 m	757 LPH @ 0.31 m



Condensate Removal Pumps

VCL SERIES Large Tank



VCL-24ULS

Applications

- For removal of condensate from an air conditioner, suitable for high efficiency, gas furnace condensation and condensing boilers

Features

- 1/8 hp motor
- Galvanized steel tank cover
- ABS tank, volute and switch cover
- 1 gallon tank capacity
- Stainless steel shaft
- Snap-action switch
- Safety switch (553201, 553211)
- Thermal overload protection
- cCSAul

Series Specifications

Capacity: 270 gph @ 1'
(1022 lph @ 0.31 m)

Shut Off: 24' (7.3 m)

Liquid Temperature: 120 °F (49 °C)

Discharge: 3/8" barbed (9.5 mm)


Impeller: Polypropylene

Electrical: 115 V, 60 Hz, 2.5A
230 V, 50/60 Hz, 1.2A

Operation: Automatic

Model Characteristics

Item #	Model	Volts	Cord	Capacity
553206	VCL-24UL	115	6'	270 GPH @ 1'
			1.8 m	1022 LPH @ 0.31 m
553201	VCL-24ULS	115	6'	270 GPH @ 1'
			1.8 m	1022 LPH @ 0.31 m
553211	VCL-24ULS	230	6'	270 GPH @ 1'
			1.8 m	1022 LPH @ 0.31 m



VCL-45ULS

Applications

- For removal of condensate from an air conditioner, suitable for high efficiency, gas furnace condensation and condensing boilers

Features

- 1/5 hp motor
- Galvanized steel tank cover
- ABS tank, volute and switch cover
- 1 gallon tank capacity
- Stainless steel shaft
- Snap-action switch
- Thermal overload protection
- 3/8" (9.5 mm) discharge copper tube
- cCSAul

Series Specifications

Capacity: 450 gph @ 1'
(1704 lph @ 0.31 m)

Shut Off: 45' (13.7 m)

Liquid Temperature: 120 °F (49 °C)

Discharge: 3/8" barbed (9.5 mm)


Impeller: Polypropylene

Electrical: 115 V, 60 Hz, 3.5A
230 V, 50/60 Hz, 1A

Operation: Automatic

Model Characteristics

Item #	Model	Volts	Cord	Capacity
553240	VCL-45ULS	115	6'	450 GPH @ 1'
			1.8 m	1704 LPH @ 0.31 m
553245	VCL-45ULS	230	6'	450 GPH @ 1'
			1.8 m	1704 LPH @ 0.31 m



ABS SERIES Shallow-Pan Tank

1-ABS



Applications

- For removal of condensate from an air conditioner drain pan or reservoir

Features

- 1/50 hp oil filled motor
- Epoxy coated cast aluminum housing and motor cover
- Nylon volute
- Stainless steel shaft
- Nitrile shaft seal
- Screened intake
- Advanced mechanical switch
- Thermal overload protection


Series Specifications

Capacity: 205 gph @ 1' (776 lph @ 0.31 m)
Shut Off: 10' (3.0 m)
Liquid Temperature: 120 °F (49 °C)
Discharge: 1/4" MNPT
Impeller: Nylon

Electrical: 115 V, 60 Hz, 1.1A
 230 V, 50/60 Hz, 0.6/0.5A
Operation: Automatic

Model Characteristics

Item #	Model	Volts	Cord	On Level	Off Level
550520	1-ABS	115	9' 2.8 m	2.25" 6.3 cm	1.5" 3.8 cm
550530	1-ABS	230	11' 3.4 m	2.25" 6.3 cm	1.5" 3.8 cm
550521	1-ABS	115	9' 2.8 m	1-3/4"	1-1/4"
550530	1-ABS	230	11' 3.4 m	1-3/4"	1-1/4"
550532	1-ABS	230	11' 3.4 m	1-3/4"	1-1/4"



2-ABS



Applications

- For removal of condensate from an air conditioner drain pan or reservoir

Features

- 1/40 hp oil filled motor
- Epoxy coated cast aluminum housing
- Includes 1/2 gallon capacity mineral filled nylon tank
- Nylon volute
- Stainless steel shaft
- Viton® shaft seal
- Hooded intake
- Advanced mechanical switch
- Thermal overload protection


Series Specifications

Capacity: 300 gph @ 1' (1136 lph @ 0.31 m)
Shut Off: 11.8' (3.6 m)
Liquid Temperature: 120 °F (49 °C)
Discharge: 1/4" MNPT
Impeller: Nylon

Electrical: 115 V, 60 Hz, 1.7A
 230 V, 50/60 Hz, 0.9/0.7A
Operation: Automatic

Model Characteristics

Item #	Model	Volts	Cord	On Level	Off Level
551020	2-ABS	115	9' 2.8 m	3" 7.6 cm	2" 5.1 cm
551030	2-ABS	230	11' 3.4 m	3" 7.6 cm	2" 5.1 cm



Condensate Removal Pumps

ABS SERIES Shallow-Pan Tank

3-ABS



Applications

- For condensate removal

Features

- 1/2 hp oil filled motor
- Epoxy coated cast aluminum housing and motor cover
- Galvanized steel tank cover
- ABS tank
- 1 gallon capacity
- Nylon volute
- Stainless steel shaft
- Thermal overload protection
- 1/2" MNPT discharge with brass check valve for 1/2" OD (12.7 mm), rigid plastic or copper
- Viton® shaft seal
- Advanced mechanical switch
- Thermal overload protection


Series Specifications

Capacity: 310 gph @ 1' (1173 lph @ 0.31 m)
Shut Off: 26' (7.9 m)
Liquid Temperature: 120 °F (49 °C)
Discharge: 1/2" MNPT (12.7 mm)
Impeller: Nylon

Electrical: 115 V, 60 Hz, 3.5A
 230 V, 50/60 Hz, 1.8/1.6A
Operation: Automatic

Model Characteristics

Item #	Model	Volts	Cord	On Level	Off Level
551320	3-ABS	115	9'	4.25"	3.25"
			2.8 m	10.8 cm	8.3 cm
551330	3-ABS	230	11'	4.25"	3.25"
			3.4 m	10.8 cm	8.3 cm



EC SERIES Mini-Split/Ductless

EC-400



Applications

- Removes condensate from ductless mini split wall mount air conditioners and fan coils

Features


- For intermittent operation, maximum 50% duty cycle
- Condensate produced in application must be no more than half the pump's flow rate for any given head
- Use with most mini-split air conditioning units up to 25,000 BTU/hr
- Self-priming pump can be placed up to 3' (.9 m) above reservoir
- Includes safety switch, suction tubing (3" x 5/32" ID) [76.2 mm x 3.96 mm], vent tubing (8" x 5/32" ID) [20.3 cm x 3.96 cm], drain tubing (3" x 1/2" ID) [76.2 mm x 12.7 mm] and tubing adapter (5/32" x 1/4" ID) [3.96 mm x 6.3 mm]

Series Specifications

Capacity: 2.5 gph @ 1' (9.5 lph @ 0.31 m)
Shut Off: 35' (10.7 m)
Electrical: 115 V, 60 Hz, 0.24A
 230 V, 60 Hz, 0.1A
Operation: Automatic

Model Characteristics

Item #	Model	Volts
553458	EC-400	230
553455	EC-400	115



TP SERIES Peristaltic



TPS

Applications

- Removes condensate from ductless mini split wall mount and cassette air conditioners and fan coils

Features


- Not affected by dust, bacteria, mold or airborne particles found in condensate
- Glass-reinforced polycarbonate pump/motor housing
- Hinged tube cover
- Extra tube assembly included
- Santoprene® tube
- Easy to replace pump tube – no tools required
- 5-minute “off” delay (TPS and TPT models)
- Impedance protected motor
- Test switch
- Double insulated, enclosed motor housing
- Wall bracket included
- Recommended for systems up to 12 kW (6 kW in tropical areas)

Series Specifications

Shut Off: 46" (14 m)
Suction Lift: 6.5' (2 m)
Inlet: 1/4" (6 mm) ID

Electrical: 230 V, 50/60 Hz, 0.06A, 13W
Alarm Contact: 5A (TPR only)

Performance Curve



Model Characteristics

Item No.	Model No.	Volts	Hertz	Amps	Watts	Shutoff (ft.)	Suction Lift	Max Flow (GPH)	Weight (lb.)	Dimensions (H x L x W)
553674	TPS	230	50/60	.06	13	46'	6.5'	2.5	2.3	4.5" x 3.8" x 3.9"
						14 m	2 m	9.46 lph	1.04 kg	114.8 mm x 95.5 mm x 98.3 mm
553675	TPT	230	50/60	.06	13	46'	6.5'	2.5	2.3	4.5" x 3.8" x 3.9"
						14 m	2 m	9.46 lph	1.04 kg	114.8 mm x 95.5 mm x 98.3 mm
553676	TPR	230	50/60	.06	13	46'	6.5'	2.5	2.3	4.5" x 3.8" x 3.9"
						14 m	2 m	9.46 lph	1.04 kg	114.8 mm x 95.5 mm x 98.3 mm
Reservoir	—	—	—	—	—	—	—	—	—	3.25" x 3.4" x 4.5"
Pump/Controller	—	—	—	—	—	—	—	—	—	82.5 mm x 86.3 mm x 114.3 mm
										3.9" x 1.5" x 1.5"
										99.0 mm x 38.1 mm x 35.6 mm

TP Series condensate pumps can be located in the ceiling void and lift water from wall, floor, ceiling or cassette air conditioning units up to 12 kW. Quieter than other condensate pumps, Little Giant TP pumps feature a totally enclosed motor (no ventilation required), “press-to-activate” switch, 5-minute “off” delay (TPS and TPT), easy to replace pump tube and mounting bracket.



TPS Series (compressor or cooling signal)

- The TPS series automatically operates when the compressor is engaged.



TPT Series (temperature signal)

- The TPT series automatically operates when there is a temperature differential of 9 °F (5 °C) in the cooling coils. The pump is programmed to operate for 5 minutes after the compressor shuts off to collect any residual condensate before stopping.



TPR Series (reservoir collection tank)

- The TPR series utilizes a reservoir collection tank to activate the pump. The TPR also includes a safety overflow option.

EC-OP-K SERIES Mini-Split/Ductless



Applications

- Removes condensate from ductless mini split wall mount and cassette air conditioners and fan coils

Features

- Pump float retainer for easy serviceability
- Clear reservoir for visual inspection of water level, float and filter
- Safety alarm ready
- 8A resistive – 250 V alarm contact
- 5/16" (8 mm) inlet tubing with universal adapter
- 5/32" (4 mm) discharge tubing with 1/4" (6 mm) adapter
- 131' (40 m) maximum horizontal distance
- 176 °F (80 °C) thermal protection
- Safety alarm ready, suitable for BMS systems

Series Specifications

Shut Off: 29' (9 m)

Ambient Temperature: 104 °F (40 °C)

Discharge: 1/4" (6 mm)

Material: Flame retardant ABS


Electrical: 230 V, 50 Hz, 20W

Fuse: 3A (recommended, not included)

Operation: Automatic

EC-OP-K

Performance Curve



Model Characteristics

The EC-OP-K has a unique design that reduces vibration and operating noise while improving sustained, maximum pumping performance making it ideal for a wide range of environments. The design also provides quieter starting and stopping of the pump motor.

The kit, model EC-OP-K comes complete with EC-OP pump, pump concealing cover, mounting bracket and all hardware necessary for fast and easy installation. A template is provided for quick and accurate location beneath any air handler.

Item#	Model	Volts	Hertz	Dimensions (in)			Weight (lb)
				Height	Length	Width	
553712	EC-OP-K	230	50/60	3.5 89 mm	8.3 201 mm	3.2 81 mm	3 1.36 (kg)



EC-OP-K Installed

Ice Machine Replacement Pumps

RIM-U



Applications

- Universal replacement unit for OEM pumps

Features

- 1/25 hp motor
- Screened intake
- NSF-listed ABS volute, base and discharge adapters
- Stainless steel shaft
- 4 lead wires, 3' (1 m) in length
- Thermal overload protection
- CSA listed

Series Specifications

Capacity: N/A

Liquid Temperature: 120 °F (49 °C)

Discharge: 5/8" (15.9 mm) Y,
1/2" (12.7 mm),
5/8" (15.9 mm),
3/4" (19 mm) and
1" (25.4 mm) OD tubing

Impeller: NSF-listed ABS

Electrical: 115/230 V, 50/60 Hz
1.5/0.75A

Model Characteristics

Item #	Model	Volts
545600	RIM-U	115/230

Impeller Diameter	Discharge Adapter (I.D. Tubing Size)	Flow - Gallons / Liters per Hour 2 ft / .6 m	
		GPH	LPH
1.75" / 44.5 mm	1/2" / 12.7 mm	290	1097
	5/8" / 15.8 mm	435	1646
	3/4" / 19.1 mm	540	2044
	1" / 24.5 mm	585	2214
1.83" / 46.5 mm	1/2" / 12.7 mm	360	1362
	5/8" / 15.8 mm	550	2081
	3/4" / 19.1 mm	700	2649
	1" / 24.5 mm	810	3066
1.95" / 49.5 mm	1/2" / 12.7 mm	385	1457
	5/8" / 15.8 mm	600	2271
	3/4" / 19.1 mm	760	2876
	1" / 24.5 mm	825	3122
2.10" / 53.3 mm	1/2" / 12.7 mm	400	1514
	5/8" / 15.8 mm	600	2271
	3/4" / 19.1 mm	700	2649
	1" / 24.5 mm	760	2876

Evaporative Cooler Pumps

CP SERIES




Applications

- For use in evaporative coolers, displays, laboratories, water transfer and other applications; replacement units for OEM equipment

Features

- Heavy duty concentric fan-cooled motor
- Corrosion-resistant one-piece steel motor shaft
- Moisture-proof windings
- Oversized sleeve bearings with large oil reservoir
- Universal mounting configurations
- Discharge elbow fits 1/2" (12.7 mm), 5/8" (15.9 mm) or 3/4" (12.7 mm) ID flexible tubing (540005, 540015); and 5/8" (15.9 mm) and 3/4" (12.7 mm) ID flexible tubing (541005, 541015, 542005 and 542015)
- Low pump down and recovery levels
- Grounded plug
- Flame retardant housing
- Snap-off volute plate for easy cleaning
- Mesh debris screen
- Thermal overload protection
- UR listed


Performance Curve CP1




Model Characteristics

Item #	Model	HP	Volts	Capacity	Shut Off	Cord	CFM Rating	Replaces
540005	CP1-115	1/70	115/127	307 GPH @ 1' 1162 LPH @ 0.31 m	9.5' 2.9 m	4' 1.2 m	5000 - 7500	CP-6500, CP-6500T, CP-651T-LLUR, CP-652T-LLUR
540015	CP1-230	1/70	230	307 GPH @ 1' 1162 LPH @ 0.31 m	9.5' 2.9 m	4' 1.2 m	5000 - 7500	CP-6500, CP-6500T, CP-651TLLUR, CP-652T-LLUR
541005	CP2-115	1/50	115	502 GPH @ 1' 1900 LPH @ 0.31 m	11' 3.4 m	4' 1.2 m	7500 - 15000	CP-10000, CP-10000UR, CP-211T-LLUR, CP-212T-LLUR
541015	CP2-230	1/50	230	502 GPH @ 1' 1900 LPH @ 0.31 m	11' 3.4 m	4' 1.2 m	7500 - 15000	CP-10000, CP-10000UR, CP-211T-LLUR, CP-212T-LLUR
542005	CP3-115	1/30	115	563 GPH @ 1' 2131 LPH @ 0.31 m	12' 3.7 m	4' 1.2 m	15000 - 21000	CP-15000, CP-15000UR
542015	CP3-230	1/30	230	563 GPH @ 1' 2131 LPH @ 0.31 m	12' 3.7 m	4' 1.2 m	15000 - 21000	CP-15000, CP-15000UR

Performance Curve CP2



Performance Curve CP3



Accessories

GKPK-SC Coil Cleaning Kit



Applications

- For effective cleaning, deliming and descaling of coils
(Coil cleaning chemicals not included)

Features

Pump:

- 1/30 hp motor
- Glass-filled polypropylene volute
- Nitrile o-ring
- Ceramic thrust washers and shaft
- Thermal overload protection

Kit:

- Includes 5 gallon polyethylene tank, cover, baffle, 2-MD-SC (special version #580523) magnet-driven pump with mounting bracket, 18' (5.5 m) of 1/2" (12.7 mm) Tygon® tubing and 10' (3 m) of 1/2" (12.7 mm) ID vinyl tubing

Uses include:

Heating - water heaters, steam converters, shell and tube heat exchangers, vessel heating applications, fin tube coils, pool heaters, unit heater cleaning, car wash heaters, and oil supply lines to fuel oil heaters
Air Conditioning - air conditioning coils, seawater applications, distillation process, compressor burnouts, outboard motor flushings, residential and commercial uses

Series Specifications

Capacity: 310 gph @ 1'
(1174 lph @ 0.31 m)


Shut Off: 14.6' (4.5 m)

Liquid Temperature: Intermittent up to 150 °F

Impeller: Glass-filled polypropylene
Electrical: 115 V, 60 Hz, 1.4A

Model Characteristics

Item #	Model	Volts	Cord
562660	GKPK-SC	115	6' 1.8 m



Auxiliary Condensate Overflow Safety Switch

Applications

- Installs in the condensate drain pan of air conditioning or refrigeration units; reliable equipment shutdown when overflow conditions are detected

Features

- Can install switch to activate audible and/or visual alarm
- ABS housing
- ABS float
- Low voltage
- Lead wires
- UR / C-CSA listing



Item #	Model	Wire	Max. VAC	Max. Amps
599122	ACS-2	18" .45 m	48 VAC/VDC	5
599123	ACS-2	72" 1.8 m	48 VAC/VDC	5
599124	ACS-3	72" 1.8 m	125-250 VAC/VDC	11

Secondary Condensate Overflow Safety Switch

Applications

- Installs in the primary drain pan's auxiliary outlet to detect downstream clogs; reliable equipment shutdown

Features

- Can install switch to activate audible and/or visual alarm
- Low voltage
- Lead wires
- Includes 3/4" MNPT (12.7 mm) x 3/4" (12.7 mm) slip adapter
- cULus listing



Item #	Model	Wire	Max. VAC	Max. Amps
14940157	ACS-5	72" 1.8 m	24VAC	5

Accessories

In-Line Condensate Overflow Safety Switch

Applications

- Installs in the drain lines to detect downstream clogs; reliable equipment shutdown

Features

- Can install switch to activate audible and/or visual alarm
- Low voltage
- Lead wires
- 3/4" (12.7 mm) plug, 3/4" (12.7 mm) slip x 3/4" (12.7 mm)
- Includes 1" x 3/4" 25.4 mm x 12.7 mm) adapter
- cULus listing



Item #	Model	Wire	Max. VAC	Max. Amps
599125	ACS-4	72" 1.8 m	24VAC	5

Reservoir Assembly



Features

- Replacement reservoir assembly for EC-400 and TPR pumps

Item #	Model
153781	Reservoir Assembly

ERC Extension Cable



Features

- 3.3' (1 m) extension cable for TPT temperature sensor and TPR and EC-400 reservoir assembly

Item #	Model
599170	ERC

T-20/25 Tubing



Features

- One carton of 25 pieces of 20' (6.01 m) length 3/8" (9.5 mm) ID VC tubing

Item #	Model
599033	T-20/25

T-3/8 Tubing



Features

- 100' (640.1 m) of 3/8" (9.5 mm) ID x 1/2" (12.37 mm) OD clear tubing

Item #	Model
599107	T-3/8

T-RPC-10 Tube



Features

- Replacement tube assembly for TPS, TPT and TPR pumps

Item #	Model
599270	T-RPC-10

PC-10 Pump Repair Kit



Features

- Replacement roller and tube kit for TP Series and PC-10

Item #	Model
599325	PC-10-PRK

Accessories

CV-2 Check Valve



Features

- For ABS Series pumps
- 1/4" FNPT (6.35 mm) to 1/4" (6.35 mm) OD tubing

Item #	Model
599061	CV-2

CV-4 Check Valve



Features

- For ABS Series pumps
- 1/2" FNPT (12.7 mm) to 1/2" (12.7 mm) OD tubing rigid plastic or copper tubing

Item #	Model
599062	CV-4

CV-35 Check Valve



Features

- For VCL-45ULS
- 3/8" (9.5 mm) rigid plastic or copper tubing on both ends

Item #	Model
599064	CV-35

CV-10 Check Valve



Features

- For VCC Series, VCMA Series and VCL-14/24 pumps
- 1/4" FNPT (6.35 mm) to 3/8" (9.5 mm) ID vinyl tubing

Item #	Model
599065	CV-10

CV-X38 Check Valve



Features

- For Condensate Pump Series VCMX
- 3/8" (9.5 mm) OD rigid plastic or copper tubing

Item #	Model
599058	CV-X38

CV-14/24 Check Valve



Features

- For VCC Series, VCMA Series and VCL-14/24 pumps
- 1/4" MNPT (6.35 mm) to 3/8" (9.5 mm) OD rigid plastic or copper tubing

Item #	Model
599069	CV-14/24

CV-15/20 Check Valve



Features

- Brass check valve for VCMA-15/20
- 1/4" MNPT (6.35 mm) to 3/8" (9.5 mm) OD rigid plastic or copper tubing

Item #	Model
599063	CV-15/20

About Our Company.

With its Little Giant brand, Franklin Electric – Water Transfer Systems (FEWTS) is a leading global supplier of water pumping systems for residential and commercial markets. The Company's product lines – sump, sewage, effluent, condensate, and industrial submersible pumps – were further expanded by its acquisition of the pump division of Monarch Industries Limited of Canada in 2007. By adding deep well submersible pumps, as well as jet, lawn sprinkler, and end suction centrifugal pumps, the acquisition complemented and broadened the Company's overall product offerings.

Parent company Franklin Electric is a global leader in the production and marketing of systems and components for the movement of water and automotive fuels. Recognized as a technical leader in its specialties, Franklin serves customers around the world in residential, commercial, agricultural, industrial, municipal, and fueling applications.

Long recognized as the world's largest manufacturer of submersible electric motors, Franklin Electric has been able to leverage its expertise in motor applications to grow and serve several different markets. The principal application for Franklin products is water well pumping systems, where the company offers pumps, motors, drives, and controls. In addition, Franklin Electric produces a vast array of products for fueling systems and the water transfer market.

With 3,500 employees worldwide, Franklin Electric is a global manufacturer with over 25 manufacturing and distribution facilities located in the United States, Germany, Czech Republic, Italy, Mexico, Canada, Australia, Brazil, South Africa, China, and Japan.

ASME



MANA

HARDI

Franklin Electric
301 North MacArthur
Oklahoma City, OK 73127
PH: 1-800-701-7894
FX: 1-800-678-7867
www.LittleGiantPump.com



Franklin Electric

Form 995505 03/12